FOE260 "6698660



FIG. 1A


131
LINE Interface Devices
145A
LOCAL MEM
145B
LOCAL MEM
145C
LOCAL MEM
145N
LOCAL MEM
134
Receive
Transmit
132
ASSP Device
ASSP Device
ASSP Device
ASSP Device
150A
150B
150C
150N
HOST Bus
139
Bridge Logic
HOST Processor
HOST Memory
138
136
140
142
BACKPLANE/ NETWORK INTERFACE BUS
130

FIG. 1B

TOE260 "66986660



FIG. 2



FIG. 3



FIG. 4



FIG. 5A


X
Y
Z
533
531
532
DATA TYPER AND ALIGNER 502
MUX 514A
MULTIPLIER M1 504A
MUX 516
COMPRESSER 506
MUX 520A
ADDER A1 510A
MUX 520B
ADDER A2 510B
MUX 522
ACCUM REGAR 512
MUX 520C
ADDER A3 510C
MUX 514B
MULTIPLIER M2 504B

FIG. 5B



FIG. 6A

610

611 MAIN OP	612 SUB OP
MULT	NOP
ADD	MIN/MAX
MIN/MAX	ADD
NOP	MULT

FIG. 6B

Patent Application Publication Oct. 26, 2006 Sheet 6 of 9 US 2006/0242214 A1

39	38	37	36	35	34	33	32	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	0	0	PS		S*	SX				SY				V/S	SA	DA	Sub-op			1	Pred		PL		Sxt		Syt		Rnd		S*	S*	S*	0	SA	DA	abs	0	0

da = +/- sx*sy	Nop	0 0 0
da = +/-(sx*sy) + sa	Add	0 0 1
da = +/-(sx*sa) + sy	Add	0 1 0
da = +/-(sx*sy) - sa	Sub	0 1 1
da = +/-(sx*sa) - sy	Sub	1 0 0
da = min(+/- sx*sy,sa)	Min	1 0 1
da = min(+/- sx*sa,sy)	Min	1 1 0
da = max(+/- sx * sy, sa)	Max	1 1 1

Lt	
Lt	
Lt	
Lt	
Gx	
Gx	
Gx	

FIG. 6C

39	38	37	36	35	34	33	32	31	30	29	28	27	26	25	24	23	22	21	20	
1	0	0	PS		S*	SX				SY				V/S	SA	DA	0	1	0	Add
																	1	0	0	Sub
																	1	1	0	Min

Add	da = +/-(mx*sa) + my
Sub	da = +/-(mx*sa) - my
Min	da = min(+/-mx*sa, my)

FIG. 6D


20-bit ISA
39 19
0 0 20-bit parallel
0 1 20-bit serial
1 0 40-bit extended
1 1 20-bit serial
Control || Control
Control # Control
DSP, extensions/Shadow
DSP # DSP
DSP Instructions
39 38 37 36 35 34 33 32 31 30 29 28 27 26 25 24 23 22 21 20
Multiply
1 0 0 PS S* SX SY V/S SA DA Sub-op
da = sx*sy
da = (sx*sy) + sa
da = (sx*sa) + sy
da = (sx*sy) - sa
da = (sx*sa) - sy
da = min(sx*sy,sa)
da = min(sx*sa,sy)
da = max(sx*sy,sa)
Add
1 0 1 PS +/- SX SY V/S SA DA Sub-op
da = sx + sy
da = sx + sy + sa
da = sx + sy; sa = sx - sy;
da = (sx + sy) * sa
da = -(sx + sy) * sa
da = min(sx+sy,sa)
da = max(sx+sy,sa)
da = ssum(sa) (sx, sy unused)
Extremum
1 1 0 PS X/N SX SY V/S SA DA Sub-op
da = ext(sx,sy)
da = ext(sx,sy,sa)
da = ext(sx,sa) * sy
da = -ext(sx,sa) * sy
da = ext(sx,sa) + sy
da = ext(sx,sa) - sy
ext(sa,ba) ? t = sx, tr = sy, tcs = tc
type-match permute
1 1 0 PS 0 SX SY x x x 1 1 1
1 1 0 PS 1 SX Type x ereg 1 1 1
Reserved
1 1 1 PS x SX SY SA DA V/S Sub-op
Nop
Add
AddSub
Mul
MulN
Min
Max
CombAdd
Nop
Ext
Mul
MulN
Add
Sub
amax
Permute
Control and specifier Extensions
19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0
Mul
0 Pred PL Sxt Syt Rnd S* S* S* 0 SA DA abs 0 0
Lt
Gx
Add/Sub
min/max
Add
0 Pred PL Sxt Syt Lt Sub-ext 0 SA DA abs 0 0
+/- +/- +/- x
x V/S Rnd Fp
tr-ctl Gx Fp
Nop (uadd)
Mul/MulN
Min/max
Ext
0 Pred PL Sxt Syt tr-ctl Gx Sub-ext 0 SA DA abs 0 0
Lt Fp
Rnd V/S
Add/sub
Mul
0 Pred PL Sxt Pctl1 0 ereg Pctl 0 0
Type/offset/permute extensions
19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0
0 Pred PL x Type:SX Type:SY 0 SA DA x 0 1
0 Pred PL Psx Permute:SX Permute:SY 0 SA DA Psy 1 0
0 Pred I/R I/R prX Offset:SX Offset:SY 0 SA DA prY 1 1
Type override
permute override
Offset override
Shadow DSP
19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0
0 Op PL op ereg ereg 1 SA DA Sub-op

FIG. 6 E

Control Instructions

	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
add,sub	L	Pred		0	0	0	RX				RY				RZ				+/-	0
max,min	L	Pred		0	0	0	RX				RY				RZ				X/N	1
Shift	L	Pred		0	0	1	RX				UI4				RZ				UI1	R/L
Logic	L	Pred		0	1	0	RX				RY				RZ				&, |	&|
Mux	L	Pred		0	1	1	RX				RY				RZ				Pd	0
mov	L	Pred		0	1	1	RX				DZ				Rxt	Dzt	0	0	0	1
addi	L	Pred		0	1	1	SI4				DZ				x	x	1	0	0	1
mov2erg	L	Pred		0	1	1	RX				unit		ereg		gd		type		1	0	1
[illegible]	L	Pred		0	1	1	RX				DZ1				DZ2				1	1
bits	L	Pred		1	0	0	UI4:POS				RZ				Rzt	UI4				0
Set2bits	L	Pred		1	0	0	UI4:POS				RZ				Rzt	UI2		0	0	1
Setbit	L	Pred		1	0	0	UI4:POS				RZ				Rzt	UI1	UI1	1	0	1
Movi	L	Pred		1	0	0	SI8								RZ				1	1
Jmp	L	Pred		1	0	1	SI9								0	Pred			0	0
Call	L	Pred		1	0	1	SI9								1	Pred			0	0
Loop	L	Pred		1	0	1	UI5 , Lcount				UI5, Lsize							UI2 Lst	0	1
Jmpi	L	Pred		1	0	1	RX				x	x	x	x	x	0	Pred		1	0
Calli	L	Pred		1	0	1	RX				x	x	x	x	x	1	Pred		1	0
Loopi	L	Pred		1	0	1	RX				x	UI5, Lsize						UI2: Lst	1	1
Test	L	Pred		1	1	0	RX				RY				PZ				=, <, >	0
Testbit	L	Pred		1	1	0	RX				UI5				PZ			B	0	1
Andp, orp	L	Pred		1	1	0	Pa		Pb		Pc				PZ			&|	1	1
Load	L	Pred		1	1	1	MX				RZ				Ext				0	0	0
Store	L	Pred		1	1	1	MZ				RX				Ext				1	0	0
eLoad	L	Pred		1	1	1	MX				RZ				1	1	1	0	0	0
eStore	L	Pred		1	1	1	MZ				RX				1	1	1	1	0	0
Extended	L	Pred		1	1	1	Bits 27:16												1	0
Logic2	L	Pred		1	1	1	RX				RY/RZ				Rxt	Ryt	&, |, &|, !		0	1
mov-erg	L	Pred		1	1	1	unit		ereg		RZ				gd		Sft		0	1	1
Crb	L	Pred		1	1	1	RX				RZ				s/m	0	0	1	1	1
Parity	L	Pred		1	1	1	RX				PZ			O/E	0	1	0	1	1	1
Stm	L	Pred		1	1	1	MZ				RX				1	1	0	1	1	1
Abs	L	Pred		1	1	1	RX				RZ				0	0	1	1	1	1
Neg	L	Pred		1	1	1	RX				RZ				0	1	1	1	1	1
step	L	Pred		1	1	1	RX				RZ				1	0	1	1	1	1
[illegible] & Set	L	Pred		1	1	1	RX				PZ			0	1	1	1	1	1	1
Reserved	L	Pred		1	1	1					0	0	0	1	1	1	1	1	1	1
Return	L	Pred		1	1	1	Pred		I-ctl		0	1	0	1	1	1	1	1	1	1
Zero-ac	L	Pred		1	1	1	ac #				1	1	0	1	1	1	1	1	1	1
eSync	L	Pred		1	1	1	RZ				0	1	1	1	1	1	1	1	1	1
Swi	L	Pred		1	1	1	UI3			0	1	1	1	1	1	1	1	1	1	1
Nop	L	Pred		1	1	1	UI3			1	1	1	1	1	1	1	1	1	1	1

<Bit1, Bits9-6> == UI5 (Shift Amount)

<Bit3, Bits13-10> == UI5 ;POS

FIG. 6F

Extended Control

	Bits 13.2 of upper half (39:20)																															
	13	12	11	10	9	8	7	6	5	4	3	2	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
Insert/Extract	RX				RZ				0	0	0	0	0	x	x	0	Rxt	Rzt	I/E	R/I	R/I	Offset·UI5					Length·UI5					0
																						x	RY				RV				x	
InsertI	UI4· length				RZ				0	0	0	1	0	x	x	0	Rzt	UI5 Position				Imm10										
Shift	RX				RZ				0	0	0	0	0	rxh	rxl	0	rzh	rzl	D	U/S	1	Shift UI5					A/L	Lt	R/L	0	Fill	1
																					0	ryh	RY									
Rotate	RX				RZ				0	0	0	0	0	x	x	0	x	x	x	x	1	Shift· UI5					1	x	R/L	1	x	1
																					0	ryh	RY									
Jmp, call	UI7							J/C	0	0	1	0	0	Pred		0	x	UI15														
dloop	UI4 outer LC				UI4 inner LC				0	0	1	1	0	x	exit	0	UI1	UI4 outer Lsize				UI4 inner Lsize				UI2 O-Lst	UI4· inner Lstart				0
pi	RX				RY				0	0	1	1	0	x	exit	0	x	UI4 outer Lsize				UI4· inner Lsize				UI2 O-Lst	UI4 inner Lstart				1
	RX				RY				0	1	0	0	0	x	x	0	0	rxh	md	ryh	+/-	=/+	RZ					I/f	rzh	rzl	s/u	s/u	0
add/sub	RX				RY				0	1	0	0	0	x	x	0	0	rxh	rxl	ryh	ryl	+/-	RZ					Lt	rzh	rzl	x	x	1
Reserved	[illegible]								[illegible]																							0
logicp	PX		D	PZ					0	1	0	0	0	x	x	0	1	T/F	T/F	T/F	&|	&|	PY				PV				x	1
Testi	RX		D	PZ					0	1	0	1	0	=,>,<		0	Imm16															
Movi	H/L	Fill			RZ				0	1	1	0	0	x	x	0	Imm16															
loadi	Type				RZ				0	1	1	1	0	x	x	0	0	0	Imm14													
storei	Type				RX				0	1	1	1	0	x	x	0	0	1	Imm14													
loadt	RX				RZ				0	1	1	1	0	x	x	0	1	Rzt	0	Type		SI10										
storet	MZ				RX				0	1	1	1	0	x	x	0	1	Rzt	1	Type		SI10										
Addi/subi	RX				RZ				1	0	+/-	0	0	Lt	s/u	0	Imm16															
mini,maxi	RX				RZ				1	0	X/N	1	0	x	x	0	Imm16															
andi,ori	RX				RZ				1	1	&|	H/L	0	x	x	0	Imm16															

Fill: Sign/Zero

Bit 15 is continuation of inner LC

andp, orp, andorp, orandp: pz = (px relop py) relop pv)

FIG. 6G


MAC:
Group
Pred
opcode
SX
SY
PL
PS
Subop
Control
Rnd
Lt
V/S
S*
S+
DA
SA
=/+
1-40-bit
2-20 ser
2-20 par
res
MUL-NOP
MUL-ADD
MUL-EXT
MUL-MUL
ARITH:
DZ
Abs
Lmt
Gx
ereg
eregs
N/X
+/-
0 0 NOP
0 1 Acc
1 0 Ext
1 1 Mac
EXT:
LOGIC:
SHIFT:
Amount
Rot
Fill
A/L
I/E
Shift
Insert/extract
Setbits
Immediate:
op
Imm2
Imm14
Imm16
Imm32
MOV
ADD
SUB
MIN
MAX
AND
OR
Test:
DPz
Branch:
Imm20
Misc:

FIG. 6H

7-bit specifier: Parallel Store, Parallel Load in DSP instructions

6	5	4	3	2	1	0
M/R						
0	0	0	SPR, s0-s15			
0	0	1	reserved			
0	1	0	ac-names			
0	1	1	gpr, r0-r15			
1	0	ptr (r0) to (r15)				off
1	1	offset, UI4				ptr

Mem[ptr] || ptr += Idx — Always postupdate
Mem[ptr + idx] — ptr: p14, p15 — Always preupdate

6-bit specifier DSP instructions

5	4	3	2	1	0
M/R					
0	0	ac-names			
0	1	gpr, r0-r15			
1	ptr (r0) to (r15)				off

Always postupdate

specifier RISC instructions

4	3	2	1	0
0	spr, s0-s15			
1	gpr, r0-r15			

4-bit specifier

3	2	1	0
gpr, r0-r15			
ptr (r0-r7)			off
ereg			

RISC instructions
20-bit DSP instructions
20-bit Shadow DSP instructions

AR

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
type				permute					CB	Idx1, UI3 (0-7)			Idx0, SI5 (-16 to 15)					ptr													

ac-names

3	2	1	0	
0	0	0	0	A0 (use type, SIMD)
0	0	0	1	A1
0	0	1	0	T
0	0	1	1	TR
0	1	0	0	A00 (unit 0)
0	1	0	1	A10
0	1	1	0	T0
0	1	1	1	TR0
1	0	0	0	SX1
1	0	0	1	SX1s
1	0	1	0	SX2
1	0	1	1	SX2s
1	1	0	0	SY1
1	1	0	1	SY1s
1	1	1	0	SY2
1	1	1	1	SY2s

SPR,

gpr-type
ereg-type
fu-ctl
pls-ctl
ob-ctl
loop-ctl
pcr
status

ereg-names

3	2	1	0	
0	0	0	0	A0
0	0	0	1	A1
0	0	1	0	T
0	0	1	1	TR
0	1	0	0	PP0
0	1	0	1	Aout
0	1	1	0	PP1
0	1	1	1	Dout
1	0	0	0	SX1
1	0	0	1	SX1s
1	0	1	0	SX2
1	0	1	1	SX2s
1	1	0	0	SY1
1	1	0	1	SY1s
1	1	1	0	SY2
1	1	1	1	SY2s

FIG. 6I

TOE280 "66962660



FIG. 7



FIG. 8
(PRIOR ART)



FIG. 9
(PRIOR ART)



FIG. 10

System Overview

TOS280 6698660



FIG. 11A


1121
start
1122
AGC
1124
Goertzel Filter
1126
TONE_ON
State ?
1128
TONE_ON_OFF
TONE_OFF
find_max(level)
1142
find_max(level)
1130
single_dual_silence_speech
1144
single_dual_silence_speech
1132
single_dual_silence_speech
1160
!(tone)
single|dual
single|dual
!silence
1146
if_same_tone
no
in_dictionary
1134
no
silence
1150
check if OFF cadence defined
no
yes
update state info - increment ON counter
1148
update state to TONE_ON
1138
update state info increment OFF counter
1162
ON & OFF cadence?
1164
NO
yes
ON cadence ?
1152
no
yes
update state to ON_OFF
1158
R
1154
declare-tone
1168
R
1154
R
1154
declare-tone
1156
R
1154
RESET
Next Frame
1140

FIG. 11B

Exemplary Filter coefficients for Goertzel Filter

frequency	cos(2*pi*f1/fs)	frequency index
350	31536	0
400	31163	1
425	30958	2
440	30829	3
480	30465	4
540	29863	5
600	29195	6
620	28958	7
660	28462	8
697	27978	9
700	27938	10
770	26955	11
780	26808	12
852	25700	13
900	24916	14
941	24218	15
1020	22802	16
1100	21280	17
1140	20487	18
1209	19072	19
1300	17120	20
1336	16324	21
1380	15332	22
1477	13084	23
1500	12539	24
1620	9634	25
1633	9314	26
1700	7649	27
1740	6644	28
1860	3595	29
1980	514	30
2040	-1029	31
2100	-2570	32
2280	-7147	33
2400	-10125	34
2600	-14875	35
3825	-32457	36

FIG. 11C

Exemplary Call Progress Tones

Frequency1	Frequency2	Call Progress Tone
350	440	ANSI T1.401 dial tone
425	0	Q.35 Dial Tone
440	480	ANSI T1.401 audible ringing
480	620	ANSI T1.401line busy tone
480	620	ANSI T1.401Reorder
400	0	Audible ringing
440	0	Dial Tone
440	0	ANSI T1.401Fast Busy Tone
440	0	Busy Tone

FIG. 11D


1169
Further Fax Processing
1180
If Fax V.21 Tone
If Modem Tone
Further Modem Processing
x[n]
Automatic Gain Control
1170
Filtering
1172
Y(n)
Energy estimation
1173
1174
X(n)
Energy estimation
1176
Decision
1177
NO
Tone Not Detected (e.g. voice)
Tone Detected
1178
1179

FIG. 11E


x[n]
y[n]
$y_1[n]$
b_{10}
b_{11}
b_{12}
$-a_{11}$
$-a_{12}$
z^{-1}
$d_{11}[n]$
$d_{12}[n]$
b_{20}
b_{21}
b_{22}
$-a_{21}$
$-a_{22}$
$d_{21}[n]$
$d_{22}[n]$

FIG. 11F


Method to detect Phase Reversals.
Determine If Difference Function is Less than Negative Threshold ?
1182
1181
No
End
yes
Determine If Difference Function is Greater than Positive Threshold ?
1184
No
End
yes
Phase Reversal Has taken Place!
1186


Energy of Signal Es
Energy of filtered signal Ef
phase reversal
the diff function
beginning of tone
1195
1193
double indication of phase-reversal
end of tone

FIG. 11G

Method for Fax V.21 Detection



FIG. 11H


Near In TD.
EC Enabled ?
1201
Yes
No
1203
NE EC FE
From FarIn Packet 1204
Tone Detection
1205
Fax Tone ?
1207
Yes
Fax Processing
1209
No
1211
EC Tone ?
Yes
No
1213
Disable EC tone
Energy< threashold
1215
No
Yes
Enable EC tone
1217
1219
VAD
1221
Silence Detected ?
yes
1223
SID Packet
no
1225
ALC
1227
DTMF/Tone Detection
1229
DTMF/ Tone Detected
yes
1231
DTMF/ Tone Packet
FarOut Packet
no
1233
G7xx Encoder
1235
Speech Packet

FIG. 12


Far In Packet
Packet Type ?
1301
1303
1304
1305
1306
Fax Packet
DTMF Packet
Tone Packet
Speech or SID Packet
1308
1310
1312
1314
Fax Demod
DTMF Generator
Tone Generator
G7xx Decoder
From NearIn
TDM
1318
NE
FE
EC
EC Enable Flag
1204
Near Out TDM

FIG. 13

TOE260 "66986660



FIG. 14


210
1520
CHn Near In
CHn Near Out
CHn Far In
CHn Far Out
Channel Execution Queue
Queue Tail Pointer Addr
Core Tail Pointer Addr
Job 1
1540
Job n
1500
1535
DMA Descriptor 1
DMA Descriptor2
CHm DMA Descriptor List
DMA Descriptor 1
DMA Descriptor2
CHn DMA Descriptor List
Channel Control Structures 1530
Dynamic Data Blocks 1515
CH n EC DD
CHn TD DD
CHn DTMF DD
CHn G.7xxx DD
CHm EC DD
CHm TD DD
CHp TD DD
1525
Scrpt_Ptr
FB + Script Header Tables
DTMF Code 1501
DTMF Constants 1504
DTMF Parameters 1507
TD Code 1502
TD Constants 1505
TD Parameters 1508
EC Code 1503
EC Constants 1506
EC Parameters 1509
1511A
1512A
Script 1 Data
Script 1 Code
Script 1 DMA Template
1511N
1513A
Script N Data
Script N Code
Script N DMA Template
1512N
1513N
Global Buffer Memory
Core Proccessors Program and Data Memory
202
204
Core 0
Core 1
Vector Area
Kernel
Script Code 1550
DTMF Code 1551
EC Code 1552
Reserved
Kernal Reserved Location
Script Data
Inter Function Block Area
DTMF Constants
DTMF Parameters
CHn DTMF Dynamic Data
EC Constants
EC Parameters
CHn EC Dynamic Data
CHn Near In Frame Data
CHn Near Out Frame Data
CHn Far In Frame Data
CHn Far Out Frame Data
Data
Reserved
Core 3
Core 2
202A
204A
202B
204B
204C
202C
204c
1560
1561
1504
1507
1562
1506
1509
1563
1564
1566
1568
1570
202D
204D
Core 2 Registers,I/O Space
413
Serial Port Address Map
Host Port Address Map
DMA_Ptr
DMA_Start
DMA_Stop
DMA_Suspend
DMA_Resume
DMA_Stat
SW_INTR
Core 2 Interrupt Registers
Semaphore (1 bit)

Fig. 15


Dynamic Data Blocks
ch 10 -DTMF
ch 102 -G.7xxx
Ch 86 - EC
ch 10 - EC
ch 10 -TD
ch 102 - EC
1515
Channel Control Structures
Channel 10
Channel 102
1530
Frame Data Buffers
ch 10, Near In
ch 10 - Near out
ch 102, Near In
ch 10 - Far Out
ch 102 - Far Out
ch 102 - Far In
ch 10 - Far In
ch 102 - Near out
1520
210
1500
AP Catalog
1525
FB & Script Header Tables
DTMF Header TABLE
EC Header TABLE
TD Header TABLE
G.xxx Header TABLE
Script 1 Header TABLE
Script X Header TABLE
DTMF Code 1501
DTMF Constants 1504
DTMF Parameters 1507
EC Code 1503
ECParameters 1509
EC Constants 1506
Script 1 Data
Script 1 Code
Script 1 DMA Template
1511A
1512A
1513A
1535
DMA Descriptor Lists
Ch 10 - DMA descriptors
Ch 102 - DMA descriptors
1540
Channel Execution Queue
job 1 = Ch10, frame 40
job n = ch 102, frame 106

FIG 16


Time
Frame Reception
Frame x
Frame x+1
Frame Processing
Frame x
Frame x+1

FIG. 17

FIG. 18


Time (arbitrary units)
CORE PROCESSOR 1
200A
Ch5,Fr10
1801A
Ch40,Fr2
1801B
Ch0,Fr102
1801C
idle
1801D
Ch87,Fr11
1801E
CORE PROCESSOR 2
200B
Ch96,Fr200
1802A
Ch200,Fr1
1802B
Ch53,Fr18
1802C
Ch67,Fr301
1802D
CORE PROCESSOR N
200N
Ch8,Fr20
1803A
Ch27,Fr30
1803B
idle
1803C
Ch54,Fr20
1803D
Ch38,Fr90
1803E